


AL 1450 RA SPECIFICATIONS & STANDARD LIST



SPECIFICATIONS:

Max people 5	Fuel Capacity 50L (Under Floor)	Standard Engine Honda BF60 AK1 LRTU or Mercury 50 ELPT
Overall Hull Length 4.50m	Beam 2.06m	Maximum Horsepower 60hp
Length on Trailer 5.45m	Side Sheet 3.0mm	Maximum Weight on Transom 120kg
Height on Trailer 1.90m	Bottom Sheet 3.0mm	Standard Dunbier Trailer Sports Centre Line 4.4M-13B
Width on Trailer 2.10m	Dry Towing Weight 820kg (approx.)	

STANDARD EQUIPMENT LIST

- CAD Designed Whittley Hull
- Factory Supplied Owner's Manual
- Local Registrations (Where Available) (Boat & Trailer)
- Pre-Delivery BMT Package
- Delivery From Closest Whittley Boating Centre
- Registration Stickers
- 3mm Flat Side Sheets
- 3mm Bottom Side Sheets
- Whittley Super Lift Hull with Reverse Chines
- Foredeck With Self Draining
- Anchor Well
- Whittley Fast Back Transom Design
- Transom Boarding Steps
- Extruded Side Decks Fully Welded
- Railblaza Trac Loader Extrusion
- Sleek Curved Walk Thru Windscreen
- Windscreen Grab Rail
- Walk Thru Dashboard Design
- Dometic Seastar Exteam Steering
- Gussi Sports Steering Wheel
- Full Carpeted Flooring Thru Out
- Floor Step Down Under Dash
- Underfloor Flotation
- Pedestal Mounted Folding Seats
- Plugs In Seat Bases x 2
- Rear Seat Box Seat / Storage & Back Rest
- Underfloor Storage With Hatch
- Wiring Harness
- Bow Rails & Bow Sprit
- Side Rails
- Side Pockets
- Glove Box
- Cleat In Anchor Well
- Transducer Bracket
- Screen In Bungs
- Australian Builders Plate
- Whittley Skipper Pack (2 x Adjustable Rod Holders
1 x Stow Pod, 1 x Versatile Drink Holder,
2 x Trac Loader Side Ports, 2 x Star Ports & Mesh Bag)
- Under Floor Fuel Tank 50L
- Paint White Interior & Exterior
- Victorian Inshore Safety Kit
- Mounted Fire Extinguisher
- Battery & Switch
- Navigation & Anchor Lights
- Bilge Pump
- Bimini Fixed (With Separate Bimini Sock)
- Rear Ladder
- Anchor, Rope & Chain Combination
- Trailer Tie Down Straps
- Trailer Spare Wheel & Bracket
- Trailer Winch
- Alloy Wheels & Black Guards
- Jockey Wheel
- Exclusive Structural 2 + 1 Year Whittley Hull Warranty
- Whittley Sports Decal Kit
- Whittley QR Code Service & Boating Accessory Decals
- Whittley Spare Wheel Cover
- Whittley Service Wallet Holder



SPECIFICATION & STANDARD EQUIPMENT PRODUCT SHEET DISCLAIMER: Every effort has been made to ensure that the information on this document is correct and up to date. However, Whittley Marine Group Pty Ltd ACN 6279 33635 ("Whittley") does not provide any warranty as to the completeness or accuracy of the information and subject to applicable laws, does not accept any liability for damages of any kind resulting from the access or use of this content. This document & information is produced as a guide only.

* The height and length on trailer measurement, can be reduced or lowered upon request, for example, a swing away draw bar option is available to reduce the overall length, please talk to your local dealer for more information. Measurements supplied are to be used as a guide only, to confirm measurements before making a purchase decision based upon these measurements, consult your Authorized Whittley Dealer or Whittley Factory Sales Representative. These measurements supplied are only to act as a guide and may vary from time to time.

** Dry towing weight is an approximate guide and is a best-case scenario, this may vary and is the approximate base package weight with no options. The addition of factory supplied options, will increase the total BMT package weight, consult your Authorized Whittley Dealer or Whittley Factory Sales Representative for more information regarding towing weights and post purchase consult your owner's manual.

*** Boat trailer packages on a mechanically braked trailer with a ATM of 2,200 kg rating and a GVM rating of 2,000 kg's, require a maximum of 10% of the package weight to be on the tow ball as down weight. For more information, please consult your owner's manual, Authorized Whittley Dealer or Whittley Factory Sales Representative for more prior to purchase.

