


AL 1740 CC SPECIFICATIONS & STANDARD LIST



SPECIFICATIONS:

Max people 5	Fuel Capacity 150L (Under Floor)	Standard Engine Honda BF135 D XRUW or Mercury 135 XL
Overall Hull Length 5.40m	Beam 2.40m	Maximum Horsepower 140hp
Length on Trailer 6.75m	Side Sheets 4.0mm	Maximum Weight on Transom 221kg
Height on Trailer 2.55m (Targa Folded)	Bottom Sheets 4.0mm	Standard Dunbier Trailer LPA 5.3M-14B
Width on Trailer 2.35m	Dry Towing Weight 1280kg (approx.)	

STANDARD EQUIPMENT LIST

- CAD Designed Whittley Super Tough Plate Hull
- Factory Supplied Owner's Manual
- Local Registrations (Where Available) (Boat & T
- Pre-Delivery BMT Package
- Delivery From Closest Whittley Boating Centre
- Registration Stickers
- 4mm 5083 High Tensile Bottom Sheets
- 4mm 5052 Side Sheets
- 4mm Bulkheads
- Frame GRID Fully Welded Hull
- Walk Thru Transom Door
- Full Height Transom With Platform
- Extruded Side Decks
- Railblaza Trac Loader Extrusion
- Enclosed Rear Transom With Twin Hatches
- Large Aluminium Anchor Well
- Raised Front Casting Deck With Access Hatches
- Two Piece Folding Centre Console
- Large Dash Fascia For Oversized Electronics
- Automatic Bilge Pump
- LED Navigation & Anchor Light
- Carpeted Timber Floor
- Underfloor Foam Flotation
- Long Range Alloy Under Floor Tank 150 L
- Heavy Duty Dive Folding Ladder
- High 32mm Bow Rails
- Heavy Duty Bow Sprit
- 32mm Transom Rails
- 32mm Side Rails
- Large Side Pocket x 2
- Riveted Aluminium Rod Holder x 4
- Welded Alloy Cleat On Transom x 2
- Welded Alloy Cleat In Anchor Locker
- Cup Holder x 2
- Sports Steering Wheel
- Helm Seat Box Upholstered
- Victorian Inshore Safety Kit
- Mounted Fire Extinguisher
- Swing Back Rest On Helm Seat
- Seadeck On Side Decks
- Electrical Switch Panel
- Transducer Bracket x 2
- Paint Inside & Out White
- Anchor Winch Bracket
- Whittley Skipper Pack (2 x Adjustable Rod Holders, 1 x Stow Pod, 1 x Versatile Drink Holder, 2 x Trac Loader Side Ports, 2 x Star Ports & Mesh Bag)
- Hydraulic Steering
- Electrical Wiring Harness & Blade Fuse Holder
- Access Panels Inside Ribs
- Saltwater Deck Wash
- Plumbed Live Bait Tank
- Stereo, Bluetooth & 2 x Speakers
- VHF, Ariel & Base
- Electric Motor Bracket
- Bait Board
- Alloy T Top & Canvas (Folding)
- Battery & Switch
- Anchor, Rope & Chain Combination
- Trailer Tie Down Straps
- Trailer Spare Wheel & Bracket
- Trailer Winch
- Alloy Wheels & Black Guards
- Jockey Wheel
- Exclusive Structural 2 + 1 Year Whittley Hull Warranty
- Whittley Sports Decal Kit
- Whittley QR Code Service & Boating Accessory Decals
- Whittley Spare Wheel Cover
- Whittley Service Wallet Holder



SPECIFICATION & STANDARD EQUIPMENT PRODUCT SHEET DISCLAIMER: Every effort has been made to ensure that the information on this document is correct and up to date. However, Whittley Marine Group Pty Ltd ACN 6279 33635 ("Whittley") does not provide any warranty as to the completeness or accuracy of the information and subject to applicable laws, does not accept any liability for damages of any kind resulting from the access or use of this content. This document & information is produced as a guide only.

* The height and length on trailer measurement, can be reduced or lowered upon request, for example, a swing away draw bar option is available to reduce the overall length, please talk to your local dealer for more information. Measurements supplied are to be used as a guide only, to confirm measurements before making a purchase decision based upon these measurements, consult your Authorized Whittley Dealer or Whittley Factory Sales Representative. These measurements supplied are only to act as a guide and may vary from time to time.

** Dry towing weight is an approximate guide and is a best-case scenario, this may vary and is the approximate base package weight with no options. The addition of factory supplied options, will increase the total BMT package weight, consult your Authorized Whittley Dealer or Whittley Factory Sales Representative for more information regarding towing weights and post purchase consult your owner's manual.

*** Boat trailer packages on a mechanically braked trailer with a ATM of 2,200 kg rating and a GVM rating of 2,000 kg's, require a maximum of 10% of the package weight to be on the tow ball as down weight. For more information, please consult your owner's manual, Authorized Whittley Dealer or Whittley Factory Sales Representative for more prior to purchase.

