CR 2180 SD SPECIFICATIONS & STANDARD LIST

Max people 6 Overall Hull Length 6.62m Length on Trailer 7.00m*

Height on Trailer 2.45m* (top windscreen) Width on Trailer 2.35m

Beam 2.35m Deadrise (at transom) 19° Fuel Capacity 110L Water Capacity 40L Dry Towing Weight 1,900kg** (approx.)

Standard Engine Volvo Penta V6 200 SX Maximum Horsepower Volvo Penta V6 200 SX Maximum Weight on Transom N/A Standard Mackay Trailer MLKR-50-T-13-M Trailer Weight Rating 2,200kg ***

CONVENIENCE STANDARD

CAD Designed Whittley Hull Factory Supplied Owner's Manual

Anchor Light LED Navigation Lights LED Front S/S Eye Bolt

Separate Self Draining Anchor Locker Stainless Steel Split Bow Rails 110 L Fuel Tank (With Breather)

40L Water Tank

Fibreglass Encapsulated Stringer System

Toughened Glass Recessed Side Lower Cabin Windows Victorian Inshore Safety Equipment & Accessory Kit

Freight & Local Delivery Charges (To Closest Australian Capital City)

Toughened Glass Recessed Upper Cabin & Front Windows

Rear Drain Plug

1 x Passenger Grab Handle 2 x Rear S/S Grab Rails Australian Builders Plate Whittley Warning Label Kit

5 Year Hull Warranty *Refer Full Warranty Policy for more information

S/S Cup Holders

Walk Around Side Decks

Integrated Stern Drive Configuration

Local Registrations (Where Available) (Boat & Trailer)

Salt Water Engine Flushing Kit

INTERIOR STANDARD

Moulded Black Dash Board Carpet On Top Of Dash Board

Plush High-Quality Carpet Through Out

Front Cabin Side Pockets Front Bunk Cushions Front Under Bunk Storage Side Pocket Cabin Storage Sports Driver & Passenger Seats

2 x S/S Poles to Hold Front Bunk Infill's Up

Bunk Infill Cushions

Diamond Non-Skid Fibreglass Rear Floor Liner

Passenger Side Carpeted Storage Area

Carpeted Storage Under Passenger & Drivers Seats

Canister Chemical Style Toilet (Stored Under Front Bunk)

Passenger & Drivers Rear Side Seats Removable with Storage

Plastic Footrests (Drivers & Passenger Sides)

Plush Fabric Front Cabin Headlining Pressurised Fresh Water Sink

Front Cabin LED Light

Esky Cooler Box

Rear Cockpit Low Down LED Lights

Drivers & Passenger Side Low Down LED Lights

Sliding Cabin Divider Curtain

Moulded Storage & Lid (At Passengers Feet)

2 x Rear Folding Side Seats

EXTERIOR STANDARD

Vynlester Blend Gel Coat for Superior Finish & Longevity

Perspex Front Hatch

Moulded Integrated Bow Sprit Whittley Front Bow Roller Moulded Rear Boarding Platforms S/S Rear Folding Boarding Ladder

S/S Boarding Rails Two Tone Hull

Tough Rubber Gunnel Fender Strip

Sports Whittley Decal Kit

4 x S/S Mooring Cleats

S/S Split Front Bollard

Chrome Polished Gunnel Caps

Pressurised Rear Shower

Windscreen Wiper (Drivers Side)

Factory Supplied Anchor, Rope & Chain Front & Rear Engine Bonnets Folding

2 x Rear LED Lights

S/S Fuel Filler & Cap

S/S Water Filler and Cap

Extended Rear Marlin Board

Bennett SLT Spring Loaded Trim Tabs

2 x S/S Flush Mount Rod Holders

Removable Rear Steps for Maximised Fishing Room Whittley Infinity Flooring on Rear Marlin Board

ELECTRICAL STANDARD

Push Button Switch Panel

Automatic Bilge Pump

Tinned Marine Grade Wire Through Out Battery Tray & Marine Grade Battery

VHF Radio & Aerial

Stereo, Bluetooth & Speakers

Push Button Blower System (For Engine Bay)

Mechanical Barrel Battery Switch

Battery Charger (Un-Mounted)

STANDARD

Custom Fitted Sports Bimini Front

Front & Side Clears

Rear Clears

7in In Rear Door

ENGINE STANDARD

Volvo Penta V6 200 Engine

SX Single Prop Drive with Alloy Prop

Engine Flushing System

Fresh Water-Cooled Engine

All Alloy Block

Variable Valve Timing Direct Fuel Injection

Mechanical Analogue Round Gauge Cluster

Mechanical Throttle Housing & Shift

Volvo Power Assisted Steering System

Volvo Sports Steering Wheel

Whittley Premium Engine Insolation Sound Proofing

TRAILER STANDARD Mackay Trailer Model # MLKR-50-T-13-M ***

Factory Spec Mackay Galvanised Dual Axle Trailer

Trailer Bunk Skids Keel Ladder Support

Drive On – Drive Off Feature

High Quality Jockey Wheel

Front & Rear Deluxe Ratchet Straps

this is suitable to customers at additional cost at purchase.

**Boat trailer packages on a mechanically braiked trailer with an ATM of 2,200 kg rating and a GVM rating of 2,000 kgs./, require 10% of the package weight to be on the tow ball as do

windn't For more information recarding this, please consult your owner's manual or Authorized Whittley Dealer or Whittley Factory Sales Representative for more information.

