SL 27 HT SD SPECIFICATIONS & STANDARD LIST

Overall Hull Length 8.55m Length on Trailer 9.70m3

Height on Trailer 3.20m* (top of hardtop)

Width on Trailer 2.49m

Deadrise (at transom) 23° Fuel Capacity 380L

Water Capacity 120L

Dry Towing Weight 3,100kg** (approx.)

Standard Engine Volvo Penta V6 250 DPS

Maximum Horsepower Volvo Penta V8 350 DPS

Maximum Weight on Transom N/A

Standard Mackay Trailer AL-70TX-14HD-HB Trailer Weight Rating 4,400 kg

CONVENIENCE STANDARD

- Factory Supplied Owner's Manual Anchor Light LED
- Navigation Lights LED
- Front S/S Eye Bolt Separate Self Draining Anchor Locker
- Stainless Steel Split Bow Rails Integrated Stern Drive Configuration
- Folding Front Engine Bonnets
- 380 L Fuel Tank (With Fuel Sender) 120 L Water Tank
- Timber Free Stringer & Transom System Self-Draining Deck Through Scuppers
- Rear Drain Plug
- Local Registrations (Where Available) (Boat & Trailer)

- Australian Builders Plate Chemical Canister Style Toilet
- Windscreen Wipers (Drivers & Passenger Side)
- Compass On Dash
- Pressurised Water System Rear Shower, Sink & Internal Shower
- Whittley Warning Label Kit Stereo, Bluetooth & Speakers

- Year Hull Warranty
 *Refer Full Warranty Policy for more information
 Victorian Inshore Safety Equipment & Accessory Kit
- Freight To Closest Whittley Factory Owned Dealership Salt Water Engine Flushing Kit
- Foam Filled Hull

INTERIOR STANDARD

- Dash Board Single Level Whitley Rubber Flooring Throughout
- Front Cabin Cushions
- Front Under Bunk Storage
- Side Pocket Cabin Storage Sports Driver & Passenger Seats (Adjustable Back & Forth)
- Moulded Fibreglass Front Cabin Bunk Liner
- Plastic Sopac Hatches for Rear Access
- Plush Fabric Front Cabin Headlining
- Bed Infill Cushions Passenger Side Grab Handle
- Moulded Galley 12 Volt Fridge (Mounted)
- Galley Storage with Door, Above Galley
- Galley Storage with Door, Under Step Light Above Galley Area
- Pressurised Sink 24 Volt Hot Plate Cooker
- Table & Bed Insert
- Lockable Cabin Door
- Pressurised Shower 2 x Rear Seats
- Dedicated Galley & Toilet/Shower Area

EXTERIOR STANDARD

- High Quality Gel Coat for Superior Finish & Longevity
- Moulded Integrated Bow Sprit
- Whittley Front Bow Roller
- Moulded Integrated Rear Boarding Platform
- Two Tone Hull
- Tough Rubber Gunnel Fender Strip
- Sports Whittley Decal Kit
- 6 x S/S Mooring Cleats
- Perspex Front Cabin Hatch
- Walk Around Side Decks Plastic Gunnel Caps
- S/S Boarding Ladder S/S Fuel Filler & Cap
- S/S Water Filler & Cap
- Flectic Winch

HARD TOP STANDARD

- Fibreglass Moulded Hard Top
- Full Length Screen & Side Sliding Windows S/S Grab Rails & 10 Rod Holders
- S/S Hard Top Support Bars
- S/S Grab Rails on Rear of Hard Top LED Light under Hard Top
- S/S Grab Rail Under Hard Top in Centre
- Electric Rear Awning
- Fresh Water Windscreen Wiper Washers 2 x Forward Facing LED Light Bars
 - 2 x Air Flow Hatches

FISHING STANDARD

- Plastic Removable Tub Kill Tank (With Folding Lids)
- 6 x S/S Flush Mount Rod Holders
- Moulded Fibreglass Flooring
- Full Length Rod Storage in Side Pockets
- Fish Measuring Ruler Cut into Rubber Flooring Plumbed Live Bait Tank

- Upholstered Side Rub Supports Under Coaming Feet Support
- 2 x S/S Grab Handles
- Rubber Matting Side Pocket Covering
- Side Door
- Push Button Over Side Hand Wash On Hull

ELECTRICAL STANDARD

- Digital Switching System
- Automatic Bilge Pump
- Tinned Marine Grade Wire Throughout
- Mechanical Barrel Battery Switch Rear Facing LED Lights Fitted to Rear of Hard Top
- Triple Battery System & VSR
- LED Side Pocket Lights
- LED Passenger & Drivers Side Lights
- VHF Radio & Aerial Front Cabin Light
- Push Button Blower System (For Engine Bay) Battery Charger (Un-Mounted)
- Battery Management Gauge On Dash
- Hot Water System
- Zip Wake Auto Trim Tabs
- LCD DVD Screen Front Cabin Speakers

- Volvo Penta V6 250 DPS Engine
- DPS Duo Prop Drive With S/S Prop's Engine Flushing System
- Fresh Water-Cooled Engine
- All Alloy Block Variable Valve Timing
- Direct Fuel Injection
- Mechanical Analogue Round Gauge Cluster
- Mechanical Throttle Housing & Shift
- Volvo Power Assisted Steering Wheel Sports Steering Wheel
- Whittley Premium Engine Insolation Sound Proofing SPECIFICATION & STANDARD EQUIPMENT PRODUCT SHEET DISCLAIMER: Every effort has be
- as a discourse lactor to planuame. The height and depth on baler measurement can be reduced or lowered upon request. For example, a swing away draw har option is available to reduce the overall length, to your load dealer for more information. The measurements supplied are to be used as a guide only and may vary from time to time. Weights and measurements listed in this will be a supplied on the property of the

CANOPY STANDARD

Storm Travel Cover (from Rocket Launchers To Rear of Boat)

- - Mackay Trailer Model # AL-70TX-14HD-HB
 - Factory Spec Mackay Aluminium Dual Axle Trailer Electric Braked Trailer
 - Spare Wheel
 - Spare Wheel Cover
 - Trailer Bunk Skids
 - Keel Ladder Support Drive On Drive Off Feature
 - High Quality Jockey Wheel
 - Front & Rear Deluxe Ratchet Straps



SL 27 HT SD SPECIFICATIONS & STANDARD LIST

SPECIFICATION & STANDARD EQUIPMENT PRODUCT SHEET DISCLAIMER: Every effort has been made to ensure that the information on this document is correct and up to late. However, withink Planter Group Plut late (LAT 93 335S). (While!) does not provide any warranty as to the completeness or accuracy of the information and subject to applicable lank, does not accept any liability for densuges of any kind resulting from the access or use of this content. This content is information is produced as a good even just plant with the Whitely week-late for further information or you total dealer below using this information.

* The height and length on traiter measurement can be reduced or lowered upon request. For example, a swing away draw but propon is available to reduce the overall length. Resea talk to your local dealers from one information. The measurements applied are to be used as a guide only and may see your from the too time, wheylight and measurement are upon the measurement and the subject to change. Weights and measurement are approximate only and are considered a guide these can vary up to just of Whittley does not their any responsibility for weights and measurement actuary between the about be deviced by the dealer or connect if this is a requested into from the connection of the size of the size of the connection of the size of the connection of the size of the connection of the size of th

** Boat trailer packages on a mechanically braked trailer with an ATM of 2,200 kg rating and a GVM rating of 2,000 kgs.", require 10% of the package weight to be on the tow ball as down eight. For more information regarding this, please consult your owner's manual or Authorized Whittley Dealer or Whittley Factory Sales Representative for more information.

