

CR 2080 SD SPECIFICATIONS & STANDARD LIST

SPECIFICATIONS:

Max people 6	Beam 2.20m	Standard Engine Volvo Penta V6 200 G SX
Overall Hull Length 6.20m	Deadrise (at transom) 19°	Maximum Horsepower Volvo Penta V6 200 G
Length on Trailer 6.90m*	Fuel Capacity 110L	Maximum Weight on Transom N/A
Height on Trailer 2.25m* (top windscreen)	Water Capacity 40L	Standard Mackay Trailer MLKR-50-T-13-M
Width on Trailer 2.30m	Dry Towing Weight 1,850kg** (approx.)	Trailer Weight Rating 2,200kg ***

CONVENIENCE STANDARD

- CAD Designed Whittley Hull
- Factory Supplied Owner's Manual
- Anchor Light LED
- Navigation Lights LED
- Front S/S Eye Bolt
- Separate Self Draining Anchor Locker
- Stainless Steel Split Bow Rails
- Integrated Rear Stern Drive Configuration
- 110 L Fuel Tank (With Fuel Sender)
- Fibreglass Stringer System
- Foam Filled Hull
- Local Registrations (Where Available) (Boat & Trailer)
- Salt Water Engine Flushing Kit
- Toughened Glass Recessed Side Lower Cabin Windows
- Toughened Glass Recessed Upper Cabin & Front Windows
- Rear Drain Plug
- 1 x Passenger Grab Handle
- 2 x Rear S/S Grab Rails
- Australian Builders Plate
- Whittley Warning Label Kit
- 5 Year Hull Warranty
- *Refer Full Warranty Policy for more information
- S/S Cup Holders
- Victorian Inshore Safety Equipment & Accessory Kit
- Freight & Local Delivery Charges (To Closest Australian Capital City)

INTERIOR STANDARD

- Moulded Black Dash Board
- Carpet On Top Of Dash Board
- Plush High-Quality Carpet Through Out
- Front Cabin Side Pockets
- Sports Steering Wheel
- Front Under Bunk Storage
- Side Pocket Cabin Storage
- Sports Driver & Passenger Seats
- Rear Side Pockets Carpeted
- Diamond Non-Skid Fibreglass Rear Floor Liner
- Passenger Side Carpeted Storage Area
- Carpeted Storage Under Passenger & Drivers Seats
- Passenger & Drivers Rear Side Seats Removable with Storage Underneath
- Plastic Footrests (Drivers & Passenger Sides)
- Plush Fabric Front Cabin Headlining
- Rear Cockpit Low Down LED Lighting
- Drivers & Passenger Side Low Down LED Lights
- Front Cabin LED Light
- Esky Cooler Box

EXTERIOR STANDARD

- Vynlester Blend Gel Coat for Superior Finish & Longevity
- Perspex Front Hatch
- Moulded Integrated Bow Sprit
- Whittley Front Bow Roller
- Moulded Rear Boarding Platforms
- S/S Rear Folding Boarding Ladder
- S/S Boarding Rails
- Rear Tow Points
- Two Tone Hull
- Tough Rubber Gunnel Fender Strip
- Sports Whittley Decal Kit
- 4 x S/S Mooring Cleats
- S/S Split Front Bollard
- Chrome Polished Gunnel Caps
- 2 x Rear LED Lights
- S/S Fuel Filler & Cap
- 2 x S/S Flush Mount Rod Holders
- Removable Rear Step for Maximized Fishing Room
- Whittley Rubber Flooring on Rear Marlin Board
- Bennett SLT Spring Loaded Trim Tabs

ELECTRICAL STANDARD

- Push Button Switch Panel
- Automatic Bilge Pump
- Tinned Marine Grade Wire Through Out
- Battery Tray & Marine Grade Battery
- Mechanical Barrel Battery Switch

CANOPY STANDARD

- None

ENGINE STANDARD

- Volvo Penta V6 200 G Engine
- SX Single Prop Drive with Alloy Prop
- Engine Flushing System
- Fresh Water-Cooled Engine
- All Alloy Block
- Variable Valve Timing
- Direct Fuel Injection
- Mechanical Analogue Round Gauge Cluster
- Mechanical Throttle Housing & Shift
- Volvo Power Assisted Steering System
- Volvo Sports Steering Wheel
- Whittley Premium Engine Insolation Sound Proofing

TRAILER STANDARD

- Mackay Trailer Model # MLKR-50-T-13-M ***
- Factory Spec Mackay Galvanised Dual Axle Trailer
- Trailer Bunk Skids
- Keel Ladder Support
- Drive On - Drive Off Feature
- High Quality Jockey Wheel
- Front & Rear Deluxe Ratchet Straps

SPECIFICATION & STANDARD EQUIPMENT PRODUCT SHEET DISCLAIMER: Every effort has been made to ensure that the information on this document is correct and up to date. However, Whittley Marine Group Pty Ltd ACN 6279 33635 ("Whittley") does not provide any warranty as to the completeness or accuracy of the information and subject to applicable laws, does not accept any liability for damages of any kind resulting from the access or use of this content. This document & information is produced as a guide only, please consult the Whittley web-site for further information or your local dealer before using this information as a deciding factor to purchase.

* The height and length on trailer measurement can be reduced or lowered upon request. For example, a swing away draw bar option is available to reduce the overall length. Please talk to your local dealer for more information. The measurements supplied are to be used as a guide only and may vary from time to time. Weights and measurements listed in this catalogue are as occur as can reasonably be determined and can be subject to change. Weights and measures are approximate only and are considered a guide these can vary up to plus 15%.

Whittley does not take any responsibility for weights and measurement accuracy therefore these should be checked by the dealer or customer if this is a requirement that is deemed critical for the use or before purchase of any vessel. To confirm the measurements before making a purchase, consult your Authorized Whittley Dealer or Whittley Factory Sales Representative.

** Dry towing weight is an approximate guide and is a best-case scenario, this may vary and is the approximate base package weight with no options. The addition of factory supplied options will increase the total Boat Motor Trailer (BMT) package weight. Consult your Authorized Whittley Dealer or Whittley Factory Sales Representative for more information regarding towing weights and post purchase consult your owner's manual. Consult generic disclaimer for more information. Boat packages on trailers with ratings over 3,500 kg will require a 70mm tow ball, this is available to customers at additional cost at purchase.

*** Boat trailer packages on a mechanically braked trailer with an ATM of 2,200 kg rating and a GVM rating of 2,000 kgs., require 10% of the package weight to be on the tow ball as down weight. For more information regarding this, please consult your owner's manual or Authorized Whittley Dealer or Whittley Factory Sales Representative for more information.

