

FF 1950 SPECIFICATIONS & STANDARD LIST

SPECIFICATIONS:		
Max people 6 Overall Hull Length 6.17m Length on Trailer 7.10m* Height on Trailer 2.45m* (top windscreen) Width on Trailer 2.22m	Beam 2.20m Deadrise (at transom) 19° Fuel Capacity 150L Water Capacity N/A Dry Towing Weight 1,680kg** (approx.)	
Standard Engine Mercury 135 EXLPT Maximum Horsepower Mercury 150 EXLPT Maximum Weight on Transom 207kg Standard Mackay Trailer MLKR-50-T-13-M Trailer Weight Rating 2,200kg ***		
CONVENIENCE STANDARD		
<ul style="list-style-type: none"> Factory Supplied Owner's Manual Anchor Light LED Navigation Lights LED Front S/S Eye Bolt Separate Self Draining Anchor Locker Stainless Steel Split Bow Rails Integrated Rear Moulded Outboard Well 150 L Fuel Tank (With Fuel Sender) Fibreglass Encapsulated Stringer System Local Registrations (Where Available) (Boat & Trailer) 	<ul style="list-style-type: none"> Recessed Side Cabin Windows (Tinted) Rear Drain Plugs Rubber Side Steps (with Whittleby Logo) Australian Builders Plate Whittleby Warning Label Kit 5 Year Hull Warranty *Refer Full Warranty Policy for more information Victorian Inshore Safety Equipment & Accessory Kit Freight & Local Delivery Charges (To Closest Australian Capital City) 	
INTERIOR STANDARD		
<ul style="list-style-type: none"> Moulded Black Dash Board Whittleby Rubber Flooring Throughout Front Cabin Side Cushions Vinyl Rear Dash Cover Sports Steering Wheel Front Under Bunk Storage 2 x Esky & Seat Cushions 	<ul style="list-style-type: none"> Side Pocket Cabin Storage Sports Driver & Passenger Seats (Adjustable Drivers Position) S/S U Bark Seats for Esky Storage Drivers and Passenger Side Pocket Storage 2 x S/S Cup Holders Passenger Side Grab Rail Upholstered Rear Back Rests 	
EXTERIOR STANDARD		
<ul style="list-style-type: none"> Vynlester Blend Gel Coat for Superior Finish & Longevity Folding Front Hatch Moulded Integrated Bow Sprit Whittleby Front Bow Roller Moulded Rear Boarding Platforms Centre Opening Acrylic Screen Moulded Rear Boarding Platforms S/S Rear Folding Boarding Ladder S/S Boarding Rails Rear Tow Points White Hull Tough Rubber Gunnel Fender Strip Sports Whittleby Decal Kit 4 x S/S Mooring Cleats S/S Split Front Bollard 2 x Gunnel Caps S/S Fuel Filler & Cap 	FISHING STANDARD	
	<ul style="list-style-type: none"> Moulded Bait Well in Floor (With Lift Up Lid) 4 x S/S Flush Mount Rod Holders Full Length Rod Storage in Side Pockets Storage Compartment above Side Pockets Fish Measuring Ruler Cut into Rubber Flooring Folding Rear Transom Access Door Fibreglass Moulded 20L Kill Tank (Drains to The Outside of Hull) 	
ELECTRICAL STANDARD		
<ul style="list-style-type: none"> Waterproof Switch Panel Raised Battery Storage Automatic Bilge Pump Tinned Marine Grade Wire Throughout Battery Tray & Marine Grade Battery 	CANOPY STANDARD	
	<ul style="list-style-type: none"> Custom Fitted Sports Bimini Alloy Rocket Launcher 6 x Alloy Rod Holders 	
ENGINE STANDARD		
<ul style="list-style-type: none"> Mercury 135 EXLPT Mechanical Steering System Sports Steering Wheel Mercury Control Box Mercury Gauges Mercury Switch Panel Mercury Water Fuel Filter Mercury Control Cables Mercury Stainless Steel Propeller 	TRAILER STANDARD	
	<ul style="list-style-type: none"> Mackay Trailer Model # MLKR-50-T-13-M *** Factory Spec Mackay Galvanised Dual Axle Trailer Spare Wheel Spare Wheel Cover Trailer Bunk Skids Keel Ladder Support Drive On – Drive Off Feature High Quality Jockey Wheel Front & Rear Deluxe Ratchet Straps 	

SPECIFICATION & STANDARD EQUIPMENT PRODUCT SHEET DISCLAIMER:

Every effort has been made to ensure that the information on this document is correct and up to date. However, Whittleby Marine Group Pty Ltd ACN 6279 33635 ("Whittleby") does not provide any warranty as to the completeness or accuracy of the information and subject to applicable laws, does not accept any liability for damages of any kind resulting from the access or use of this content. This document & information is produced as a guide only, please consult the Whittleby website for further information or your local dealer before using this information as a deciding factor to purchase.

* The height and length on trailer measurement can be reduced or lowered upon request. For example, a swing away draw bar option is available to reduce the overall length. Please talk to your local dealer for more information. The measurements supplied are to be used as a guide only and may vary from time to time. Weights and measurements listed in this catalogue are as occur as can reasonably be determined and can be subject to change. Weights and measures are approximate only and are considered a guide these can vary up to plus 15%.

Whittleby does not take any responsibility for weights and measurement accuracy therefore these should be checked by the dealer or customer if this is a requirement that is deemed critical for the use or before purchase of any vessel. To confirm the measurements before making a purchase, consult your Authorized Whittleby Dealer or Whittleby Factory Sales Representative.

** Dry towing weight is an approximate guide and is a best-case scenario, this may vary and is the approximate base package weight with no options. The addition of factory supplied options will increase the total Boat Motor Trailer (BMT) package weight. Consult your Authorized Whittleby Dealer or Whittleby Factory Sales Representative for more information regarding towing weights and post purchase consult your owner's manual. Consult generic disclaimer for more information. Boat packages on trailers with ratings over 3,500 kg will require a 70mm tow ball, this is available to customers at additional cost at purchase.

*** Boat trailer packages on a mechanically braked trailer with an ATM of 2,200 kg rating and a GVW rating of 2,000 kgps, require 15% of the package weight to be on the tow ball as down weight. For more information regarding this, please consult your owner's manual or Authorized Whittleby Dealer or Whittleby Factory Sales Representative for more information.

